

Versatile, portable socket base for REID's *PORTA-DAVIT 500* systems.



500KG
WLL



1
Persons



Various Configurations
& Bagged



EN795
90°, 180° & 360°



A truly innovative extension to the REID socket family to further support the flexible use of the *PORTA-DAVIT 500* range.

The most convenient socket without any need for a fixed socket installation.

PORTA-BASE Information:

- **GOODS WLL** Up to 500kg at a max. 1000mm radius
- **PERSONNEL WLL** Up to 120kg
- **PORTABLE** Packed in heavy duty protective bags for easy transportation and storage
- **SPECIFICATIONS**
 - Adjustable feet for uneven surfaces with spirit level fitted to each leg
 - For use with 65mm socket diameter
 - Suitable for clean environments

PORTA-BASE is currently not suitable for use with socket extensions, *PORTA-DAVIT QUANTUMs* or *T-DAVITS*.



Available as a 90° and 180°, as well as the 270° counterbalanced version with up to 1000mm radius.

The flexible socket option for *PORTA-DAVIT 500 (R)*:

The portable socket assembly systems for *PORTA-DAVIT* eliminates installation and testing costs and allows for operation where fixed sockets are not possible or convenient.

WLL 500kg at a max 1000mm radius of davit operation with WLL 120kg for personnel lifting/fall protection.

Adjustable feet for uneven surfaces with anodised legs and yellow powder coat paint to the socket and tie bars for protection.

Manual handling compliance, assembled without tools and CE approved.

90°, 180° & 360° as well as the 270° Counterbalance versions, with up to 1000mm radius, are available. The *PORTA-BASE* unit is to be used with a restricted radius *PORTA-DAVIT 500R* series **ONLY** and not with Socket Extensions.



PORTA-BASE 90°

Lightweight & portable 65mm diameter socket foundation for the *PORTA-DAVIT 500R*:

- WLL 500kgs goods, WLL120kg personnel
- Adjustable legs with feet for levelling
- Complete with two heavy-duty bags for transportation, of weight 28kg and 10kg for the 90-degree



PORTA-BASE 180°

Lightweight & portable 65mm diameter socket foundation for the Reid *PORTA-DAVIT 500R*:

- WLL 500kgs goods, WLL120kg personnel, also available in 90° & 360° configuration
- Adjustable legs have feet for levelling
- Complete with two heavy-duty bags for transportation, of weight 42kg and 10kg for the 180-degree



PORTA-BASE 360°

Lightweight & portable 65mm diameter socket foundation for the *PORTA-DAVIT 500R*:

- WLL 500kgs good, WLL120kg personnel
- Comprises central hub/socket, leg retention plate, 4 x legs with adjustable feet for levelling and 8 x linchpins
- Complete with three heavy-duty bags for ransportation, of weight 28kg, 28kg and 10kg



PORTA-BASE 270°

Counter-Balance portable 65mm diameter socket foundation for the *PORTA-DAVIT 500R* systems:

- 800-1000mm davit operating radius
- 180-degree operating arc
- Rated WLL 120kgs for personnel lifting and rated WLL 250kg for goods lifting
- Adjustable legs for levelling with a spirit level fitted to each leg Baskets attached to the legs of the *PORTA-BASE* to utilise 18 off, 20kg hand weights
- Supplied complete in two heavy duty bags for transportation, of weight 28kg and 15kg and 2 weight baskets of 20kg each



E&OE
PBPO/EN/V3/2019/04

