

# PORTA-GANTRY® RAPIDE

Versatile and reliable, REID's sockets should be your first choice.

## Accessories

Manual chain blocks and winches, as well as electrical and air hoist alternatives:



Please discuss your overall requirements with REID Lifting.

### Chain Block (Yale CB0500-360°)

Manual Chain block rated to WLL 500 kg, complete with 3.0m of load chain and 2.5m hand chain. The chain block has a unique design for operation of the block at any angle to the load, allowing for safe operation from the side of the load rather than a traditional system (requiring the chain to be pulled from directly underneath the chain block).

A load chain container, additional load chain and additional hand chain can be supplied if required.

Now available with Overload Protection as an option.



### Electric Chain Hoist (CMLS500)

- Rated to WLL 500kg with 110V single phase power and hook suspension to suit PORTA-GANTRY
- The unit has a duty rating of 50%, a hoist speed of 4.0mpm and a minimum hook to hook dimension of 413mm
- Standard hoist with 3m HoL weighs approximately 29kg
- Also available at 240v single phase or 400v 3ph 50Hz, with hoist speed of 4m/min
- Weight = 26Kg + 0.9Kg (additional load chain per metre)



### Options on Lodestar Chain Hoist

- Additional load chain available and to be specified
- Load chain container
- Weather proof jacket

Tel: +44 (0)1291 620796 [www.reidlifting.com](http://www.reidlifting.com)

[www.reidlifting.com](http://www.reidlifting.com)

**REID**  
LIFTING  
LIGHTWEIGHT | PORTABLE | SAFE