

PORTA-DAVIT[®] 500

Easy transport and manual assembly without compromising on strength or safety (up to 500kg). Custom configurations with industry-leading delivery times.

Standard Configurations

Below are some typical system configurations for PORTA-DAVIT 500. However, the product is entirely customisable to meet your specific needs.

PORTA-DAVIT 500 (PDSSF0500-1200)

- Rated to WLL 500kg
- Operating radius: 800-1200mm under load
- Davit weight: 24kg
- Conveniently contained in 1.4m carry bag
- Height from base to lifting eye: 1968mm



PORTA-DAVIT 500+OP (PDSSF0500-1200)

- Rated to WLL 500kg
- Operating radius: 800-1200mm under load
- Davit weight: 24kg
- Conveniently contained in 1.4m carry bag
- Height from base to lifting eye: 1968mm
- With overload protection chain hoist



PORTA-DAVIT 500W (PDWSF0500-1200)

configured ready for a range of winch options, including personnel lifting

- Rated to WLL 500kg for goods and 120kg for personnel lifting
- Operating radius: 800-1200mm
- Rigid aluminium backstay
- Sheaved davit head with dual shackle points
- Conveniently contained in two carry bags (1.65m and 1.3m), each weighing less than 25kg for manual handling requirements
- Height from base to winch wire: 1930mm



The PORTA-DAVIT 500W can be operated as either a standard davit with chain-block lifting, or with a winch option mounted with a simple winch connection bracket.

Tel: +44 (0)1291 620796 www.reidlifting.com

www.reidlifting.com

REID
LIFTING
LIGHTWEIGHT | PORTABLE | SAFE

PORTA-DAVIT[®] 500

Easy transport and manual assembly without compromising on strength or safety (up to 500kg). Custom configurations with industry-leading delivery times.

Standard Configurations

Below are some typical system configurations for PORTA-DAVIT 500R (restricted radius 1000mm for use with PORTA-BASE). However, the product is entirely customisable to meet your specific needs.

PORTA-DAVIT 500R (PDSSF0500-1000)

- Rated to WLL 500kg
- Operating radius: 800-1000mm under load
- Davit weight: 24kg
- Conveniently contained in 1.4m carry bag
- Height from base to lifting eye: 2050mm



PORTA-DAVIT 500RW (PDWSF0500-1000)

configured ready for a range of winch options, including personnel lifting

- Rated to WLL 500kg for goods and 120kg for personnel lifting
- Operating radius: 800-1000mm
- Rigid aluminium backstay
- Sheaved davit head with dual shackle points
- Conveniently contained in two carry bags of (1.65m and 1.3m), each weighing less than 25kg for manual handling requirements
- Height from base to winch wire: 1977mm



The PORTA-DAVIT 500RW can be operated as either a standard davit with chain-block lifting, or with a winch option mounted with a simple winch connection bracket.

Tel: +44 (0)1291 620796 www.reidlifting.com

www.reidlifting.com

REID
LIFTING
LIGHTWEIGHT | PORTABLE | SAFE

PORTA-DAVIT[®] 500

Easy transport and manual assembly without compromising on strength or safety (up to 500kg). Custom configurations with industry-leading delivery times.

Standard Configurations

Below are some typical system configurations for PORTA-DAVIT 350EX (extended 1500mm radius system). However, the product is entirely customisable to meet your specific needs. Below are some typical system configurations for the PORTA-DAVIT 350EX - extended 1500mm radius system.

PORTA-DAVIT 500RW (PDWSF0500-1000)

extended jib crane

- Rated to WLL 350kg
- Operating radius: 800-1500mm under load
- Davit weight: 28kg
- Conveniently contained in 1.4m carry bag
- Height from base to lifting eye: 2330mm



PORTA-DAVIT 350EXW (PDWSF0350-1500)

configured ready for a range of winch options

- Rated to WLL 350kg
- Operating radius: 800-1500mm
- Rigid aluminium backstay
- Sheaved davit head with dual shackle points
- Combined weight of davit and winch: 35kg
- Conveniently contained in two carry bags (1.65m and 1.3m), each weighing less than 25kg
- Height from base to lifting eye: 2330mm



The PORTA-DAVIT 360EXW can be operated as either a standard davit with chain-block lifting, or with a winch option mounted with a simple winch connection bracket.

N.B. The PORTA-DAVIT operating radius range quoted is given 'under load'. If full radius is required under light loads then the solid backstay option should be considered.

Tel: +44 (0)1291 620796 www.reidlifting.com

www.reidlifting.com

REID
LIFTING
LIGHTWEIGHT | PORTABLE | SAFE